

Smooth Flow High Speed Rotary Screens



TS Manufacturing Co.

SOLUTIONS

Printed in Canada Imprimé au Canada

Specifications

All specifications subject to change without notice



T.S. Rotary Screens are available in standard sizes ranging from 12 to 66 units*. The counter-balanced design allows for high speed operations and lowered equipment fatigue. The durable construction incorporates Tie Rod mounting and Heavy Duty, double taper roller bearings for maximum durability and reduced maintenance.

With T.S. Manufacturing Co.'s over 30 years of experience and inhouse engineering department, every screen can be customized to suit your particular application.

Specifications

From 12 to 66 units capacity*

Mounted on 4 - tie rods with universal joints

Orbital action

Multi Screen levels

Standard 1800 R.P.M. motor, T.E.F.C.

Heavy Duty Double Taper Roller bearings

Self contained counterweight

Frame of structural steel tubing

Easy to install, operate, and maintain

*(1 unit = 200ft³ / ~ 6 m³)

Options:

Multiple Screens and Sizes

Discharge Spouts and Configuration

Built in Cyclone feeder

Punch Plate Screens in Round, Square, and Oblong Shape

Woven Wire Screens

Custom Screen Sizing

Fines can be fed into a T.S. High Pressure Pneumatic Conveying System

Economy Chipping / Screening Systems are also available



TS Manufacturing Co.

(Div. of 381572 Ontario Limited)

2 Fleetwood Road Lindsay, ON K9V 4S5

Tel : (705) 324-3762 Fax : (705) 324-6482

www.tsman.com sales@tsman.com

SOLUTIONS