Bandmill Systems





TS Manufacturing Co.

Solutions

Specifications

All specifications subject to change without notice



Available in sizes of 48", 60", 72", 84".

T.S. Manufacturing Bandmills provide greater cutting accuracy resulting in reduced sawdust & improved recovery

Fabricated and Stress Relieved Steel Construction

Fabricated Steel Wheels allow for safer operation with less Total Cost of Ownership than Cast Wheels

Available in Vertical, Slant, and Horizontal Arrangements

Patented Tilt and Strain Mechanism with less moving parts and Nitrogen Charging offers quickest response times in industry

High Strain System Designed for up to 30,000 Lbs Strain

Narrow, Double Column profile increases stiffness, and decreases arbor stress to hold precision alignments longer and allows for close coupling in multi saw layouts.

Oversized arbors with double spherical roller bearings

Bandmill is Dynamically Balanced to ensure trouble free operation

Hydraulic saw tracking

Options:

Hydraulically operated wheel quard

Regenerative or Disc Braking Systems

Custom Guide Mounting, including Swing Away Arms, Rigid Guide Arms, Automatic Guide Positioning

Machined Steel Slat bed or Take Away Belt

Spray mist lubrication system

Available in Vertical, Slant, Horizontal Arrangements

Narrow design ideal for Multi Saw Systems

Extended Saw Throat is available for Specific Applications



TS Manufacturing Co.
(Div. of 381572 Ontario Limited)
2 Fleetwood Road Lindsay, ON K9V 4S5
Tel: (705) 324-3762 Fax: (705) 324-6482
www.tsman.com sales@tsman.com

Solutions

This equipment is covered by: US PATENT 5,819,630
CANADIAN PATENT 2,176,176