



TS Rotary Screens are available in standard sizes ranging from 12 to 66 units*. Their counter-balanced design allows for high speed operations and lower equipment fatigue. The durable construction incorporates tie rod mounting and heavy duty, double taper, roller bearings for maximum durability and reduced maintenance.

With TS Manufacturing's 40+ years of experience, and in-house engineering department, every screen can be customized to suit your particular application.

*(1 unit = 200ft³ / ~ 6 m³)



Specs

- Mounted on 4 tie rods with universal joints
- Orbital action
- Multiple screen levels
- Standard 1800 rpm motor, TEFC
- Heavy duty double taper roller bearings
- Self contained counterweight
- Frame of structural steel tubing
- Easy to install, operate, and maintain



Options

- Multiple screens and sizes
- Discharge spouts and configuration
- Built in cyclone feeder
- Punch plate screens in round, square, & oblong shapes
- Woven wire screens
- Custom screen sizing
- Fines can be fed into a TS High Pressure Pneumatic Conveying System
- Economy chipping / screening systems are also available

www.tsman.com
Visit our website to find out more about TS Chip Screens.



TS Manufacturing
2 Fleetwood Rd, Lindsay, ON K9V 6H4 Canada
Tel: +1 705 324 3762 | Fax: +1 705 324 6482